



CPS® Automotive

AR2700 SERIES REFRIGERANT RECOVERY/ RECYCLING SYSTEM

FEATURES AND BENEFITS:

- Semi-automatic, easy-to-use Recovery, Recycle, Evacuate and Recharge machine
- Utilizes manual ball valves in place of solenoids, making the AR2700 impervious to contamination and sealants
- Simple operation for oil waste and air purge
- Microprocessor-controlled recharge makes the AR2700 accurate to 1/10 oz (4 grams)
- Easy-to-read high and low pressure gauges
- High efficiency 6 CFM vacuum pump will dehydrate the system to 50 microns
- Durable all steel construction
- The AR2700 can be programmed for 50 lbs, 90 lbs, 40 kg tank
- Comes with a 50 lbs tank included with the purchase of an AR2700
- 115 Volts, 50/60 HZ, single phase, PSI/KPa gauges
- 1 year warranty



CPS GLOBAL HEADQUARTERS

3600 Enterprise Way
Miramar, Florida 33025, USA

FOR MORE INFORMATION CALL:

Toll Free: 1-800-277-3808
Telephone: 305-687-4121

www.cpsproducts.com

CPS reserves the right to make changes to, or discontinue any product or service identified in this publication without notice. CPS advises its customers to ensure they have obtained the latest and most current version of any relevant information before placing any orders. ©2015 CPS PRODUCTS. ALL RIGHTS RESERVED.



Models	AR2700	AR2700M	AR2700TA	AR2700TA10
Compressor	12.67 cc Twin Cylinder Oil-less			
Tank Size	50lb			90lb
Heater Band	No	No	Yes	Yes
Condensor	No	No	Yes	Yes
Dimensions	22" W x 24.5" D x 42" H			
Weight	120 lbs/54.5 kg (not including tank)			
Operating Range	32°F (0°C) to 120° F (49° C)			
Power	115 VAC 60 Hz 1Ph			
Power Consumption	500W			
Suction Pressure Gauge	-30 inch Hg to 125 PSIG			
Discharge Pressure Gauge	0 to 500 PSIG			
Filtration	16 cubic inch drier w/ moisture indicator			
Manual Control Valves	Ball Type Valves to control HI, LO, Recover, and Vacuum			
Charging Valve	12 VDC Solenoid Valve			
Construction	1" Heavy duty tubular frame construction; 10" pneumatic wheels, 4.5" swivel casters			
Overload Protection	15A Thermal Breaker			
High Pressure Shut-off	450 PSIG (30 bar)			
Refrigerants*	R134a, R12, R22, R502, R4040a, R402a, R401a, R407c, R409a			
Single or Multiple Refrigerant	Single	Multiple	Single	Single
Pack Size	43" X 25 ½" X 28" (1092.2 x 647.7 x 711.2 mm)			
Packaging UPC	750377984273	750377984280	750377116322	750377119149
Shipping Box Size (H x W x D)	43" X 25 ½" X 28" (1092.2 x 647.7 x 711.2 mm)			
Quantity Of Packs/Shipping Box	1			
Shipping Box Weight	230 lbs	230 lbs	230 lbs	240 lbs
Pallet Size (H x W x D)	28" x 24" x 5" (711.2 x 609.6 x 127 mm)			
Quantity Of Shipping Boxes/Pallet	1			
North American HTS Code	8414.80.00.00	8414.80.00.00	8414.80.00.00	8414.80.00.00
Product Warranty	1 Year			

*The AR2700, AR2700TA and AR2700TA10 do not contain a pump down valve and is meant for single refrigerant operation. The AR2700M contains a pump down valve for multiple refrigerant usage. Mixing of refrigerants will cause the user economic loss.